

**Product Summary**

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	$I_D$
-100V	35mΩ@-10V	-25A
	45mΩ@-4.5V	


**Feature**

- $V_{DS}$  -100V
- $I_D$  -25A
- $R_{DS(ON)}$ ( at  $V_{GS}=10V$ ) < 50 mohm
- Fast Switching

**Application**


- Motor control
- Switching Regulators
- Isolated DC/DC convertor
- Alertor

**Package**




**PDFNWB5X6-8L**

### Circuit diagram



### Marking



**010P35G =Device Code**  
**\* =Month Code**

### Absolute maximum ratings

( $T_a=25^{\circ}\text{C}$  unless otherwise noted)


Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	-100	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current-Continuous	$I_D$	-25	W
Drain Current – Pulsed <sup>1</sup>	$I_{DM}$	-100	A
Power Dissipation ( $T_C=25^{\circ}\text{C}$ )	$P_D$	100	W
Thermal Resistance Junction to Case	$R_{\theta JC}$	1.25	$^{\circ}\text{C}/\text{W}$
Storage Temperature Range	$T_{STG}$	-55~ +150	$^{\circ}\text{C}$
Operating Junction Temperature Range	$T_J$	-55~ +150	$^{\circ}\text{C}$

## Electrical characteristics


( $T_A=25^\circ\text{C}$ , unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
<b>Static Characteristics</b>						
Drain-source breakdown voltage	$BV_{DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-100			V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS} = -100V, V_{GS} = 0V$			-1	$\mu A$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS} = \pm 20V, V_{DS} = 0V$			$\pm 100$	$\mu A$
Gate threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-1	-1.6	-2.5	V
Static Drain-Source on-Resistance	$R_{DS(on)}$	$V_{GS} = -10V, I_D = -15A$		35	50	$m\Omega$
		$V_{GS} = -4.5V, I_D = -10A$		45	65	
<b>Dynamic characteristics<sup>4</sup></b>						
Total Gate Charge	$Q_g$	$V_{GS} = -10V, V_{DS} = -20V, I_D = -12A$		96		nC
Gate-Source Charge	$Q_{gS}$			15		
Gate-Drain Charge	$Q_{gd}$			13		
Turn-On Delay Time	$T_{d(on)}$	$V_{GS} = -10V, V_{DD} = -20V, I_D = -20A, R_{GEN} = 3\Omega$		11		nS
Rise Time	$T_r$			17		
Turn-Off Delay Time	$T_{d(off)}$			37		
Fall Time	$T_f$			22		
Input Capacitance	$C_{iss}$	$V_{DS} = -20V, V_{GS} = 0V, f = 1MHz$		6300		$\mu F$
Output Capacitance	$C_{oss}$			220		
Reverse Transfer Capacitance	$C_{rss}$			55		
<b>Drain-Source Diode Characteristics</b>						
Continuous Source Current	$I_s$	$V_G = V_D = 0V$ , Force Current			-30	A
Diode forward voltage	$V_{SD}$	$V_{GS} = 0V, I_s = -1A$			-1.2	V


Typical Characteristics




Output Characteristics




Transfer Characteristics




$R_{DS(ON)} - I_D$



$R_{DS(ON)} - V_{GS}$




$I_S - V_{SD}$



Threshold Voltage

PDFNWB5X6-8L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	3.910	4.110	0.154	0.162
E1	3.375	3.575	0.133	0.141
D2	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
$\theta$	10°	12°	10°	12°