

Product Summary

| $V_{(BR)DSS}$ | $R_{DS(on)TYP}$ | I_D |
|---------------|-----------------|-------|
| 150V | 6.7mΩ@10V | 130A |


Feature

- Fast Switching
- Low Gate Charge and Rdson
- 100% Single Pulse avalanche energy Test

Applications


- Power switching application
- DC-DC Converter
- Power Management

Package




TO-220-3L-C(1:G 2:D 3:S)

Circuit diagram



Marking



015N06GH : Product code
****** : Week code

Absolute maximum ratings

(T_a=25°C unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|--|-----------------------------------|-----------|-------|
| Drain-Source Voltage | V _{DS} | 150 | V |
| Gate-Source Voltage | V _{GS} | ±20 | V |
| Continuous drain current (T _C = 25°C) | I _D | 130 | W |
| Pulsed Drain Current | I _{DM} | 520 | A |
| Power Dissipation (T _C = 25°C) | P _D | 280 | W |
| Single Pulse Avalanche Energy ¹ | E _{AS} | 1056 | mJ |
| Thermal Resistance Junction- Case | R _{θJC} | 0.44 | °C/ W |
| Operation and storage temperature | T _{STG} , T _J | -55~ +150 | °C |

Electrical characteristics







(T_A=25°C, unless otherwise noted)






| Parameter | Symbol | Test Condition | Min. | Typ. | Max. | Unit |
|---|---------------------|---|------|------|------|------|
| Static Characteristics | | | | | | |
| Drain-source breakdown voltage | BV _{DSS} | V _{GS} = 0V, I _D =250μA | 150 | | | V |
| Drain Cut-Off Current | I _{DSS} | V _{DS} =120V,V _{GS} = 0V | | | 1 | uA |
| Gate-body leakage current | I _{GSS} | V _{GS} = ±20V , V _{DS} =0V | | | ±0.1 | uA |
| Gate threshold voltage | V _{GS(th)} | V _{DS} =V _{GS} , I _D =250μA | 2 | 3 | 4 | V |
| Drain-Source ON Resistance | R _{DS(on)} | V _{GS} =10V, I _D =20A | | 6.7 | 8.5 | Ω |
| Dynamic characteristics ⁴ | | | | | | |
| Input Capacitance | C _{iss} | V _{DS} =75V,V _{GS} =0V, f=1MHz | | 5280 | | pF |
| Output Capacitance | C _{oss} | | | 653 | | |
| Reverse Transfer Capacitance | C _{rss} | | | 24 | | |
| Switching Characteristics | | | | | | |
| Total Gate Charge(4.5V) | Q _g | V _{DS} =75V, V _{GS} =10V, I _D =70A | | 80 | | nC |
| Gate-Source Charge | Q _{gS} | | | 33 | | |
| Gate-Drain Charge | Q _{gd} | | | 21 | | |
| Turn-On Delay Time | T _{d(on)} | V _{GS} =10V, V _{DS} =75V, R _L =3Ω, R _G =4.7Ω | | 26 | | nS |
| Rise Time | T _r | | | 35 | | |
| Turn-Off Delay Time | T _{d(off)} | | | 45 | | |
| Fall Time | T _f | | | 17 | | |
| Drain-Source Body Diode Characteristics | | | | | | |
| Source-Drain Diode Forward Voltage | V _{SD} | I _S = 1A, V _{GS} = 0V | | | 1.2 | V |

Note :


1. E_{AS} is tested at starting T_J = 25°C, V_{DD} =75V, V_{GS} = 10V, L = 0.5mH, R_G=25Ω ;

Typical Characteristics





TO-220-3L-C Package Information



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|--------|----------------------|-------|
| | Min. | Max. | Min. | Max. |
| A | 4.400 | 4.600 | 0.173 | 0.181 |
| A1 | 2.250 | 2.550 | 0.089 | 0.100 |
| b | 0.710 | 0.910 | 0.028 | 0.036 |
| b1 | 1.170 | 1.370 | 0.046 | 0.054 |
| c | 0.330 | 0.650 | 0.013 | 0.026 |
| c1 | 1.200 | 1.400 | 0.047 | 0.055 |
| D | 9.910 | 10.250 | 0.390 | 0.404 |
| E | 8.950 | 9.750 | 0.352 | 0.384 |
| E1 | 12.650 | 13.050 | 0.498 | 0.514 |
| e | 2.540 TYP. | | 0.100 TYP. | |
| e1 | 4.980 | 5.180 | 0.196 | 0.204 |
| F | 2.650 | 2.950 | 0.104 | 0.116 |
| H | 7.900 | 8.100 | 0.311 | 0.319 |
| h | 0.000 | 0.300 | 0.000 | 0.012 |
| L | 12.900 | 13.400 | 0.508 | 0.528 |
| L1 | 2.850 | 3.250 | 0.112 | 0.128 |
| V | 6.900 REF. | | 0.276 REF. | |
| Φ | 3.400 | 3.800 | 0.134 | 0.150 |