

## Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	$I_D$
40V	20mΩ@10V	20A
	27mΩ@4.5V	
-40V	34mΩ@-10V	-18A
	45mΩ@-4.5V	


## Feature

- High density cell design for ultra low Rdson
- Fully characterized avalanche voltage and current
- Fast Switching Speed

## Application


- Load switching
- Inverters
- Power Management

## Package




PDFNWB5×6-8L

## Circuit diagram



## Marking



4023C : Product code  
 \* : Month code.

## Absolute maximum ratings

( $T_a=25^\circ\text{C}$  unless otherwise noted)

Parameter	Symbol	Value		Unit
		N-Channel	P-Channel	
Drain-Source Voltage	$V_{DS}$	40	-40	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	$\pm 20$	V
Continuous Drain Current( $T_c=25^\circ\text{C}$ )	$I_D$	20	-18	A
Pulsed Drain Current	$I_{DM}$	80	-72	A
Maximum Power Dissipation( $T_c=25^\circ\text{C}$ )	$P_D$	25		W
Thermal Resistance from Junction to Case	$R_{\theta JC}$	5		$^\circ\text{C}/\text{W}$
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	$-55 \sim +150$		$^\circ\text{C}$

## N-Electrical characteristics

( $T_A=25^\circ\text{C}$ , unless otherwise noted)







Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{(\text{BR})\text{DSS}}$	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$	40			V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS} = 32\text{V}, V_{GS} = 0\text{V}, T_J = 25^\circ\text{C}$			1	$\mu\text{A}$
Gate-Body Leakage Current	$I_{GSS}$	$V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$			$\pm 100$	$\mu\text{A}$
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	1	1.5	2.5	V
Drain-source on-resistance	$R_{DS(\text{on})}$	$V_{GS} = 10\text{V}, I_D = 10\text{A}$		20	25	$\text{m}\Omega$
		$V_{GS} = 4.5\text{V}, I_D = 8\text{A}$		27	36	
<b>Dynamic Characteristics</b>						
Input capacitance	$C_{iss}$	$V_{DS} = 15\text{V}, V_{GS} = 0\text{V}, f = 1\text{MHz}$		1061		$\text{pF}$
Output capacitance	$C_{oss}$			110		
Reverse transfer capacitance	$C_{rss}$			95		
Total gate charge	$Q_g$	$V_{DS} = 15\text{V}, V_{GS} = 10\text{V}, I_D = 10\text{A}$		23		$\text{nC}$
Gate-source charge	$Q_{gs}$			3.3		
Gate-drain charge	$Q_{gd}$			5.3		
<b>Switching Characteristics</b>						
Turn-on Delay Time	$T_{d(on)}$	$V_{DD} = 15\text{V}, V_{GS} = 10\text{V}, R_G = 3.3\Omega, I_D = 6\text{A}$		5.5		$\text{nS}$
Turn-on Rise Time	$T_r$			14		
Turn-Off Delay Time	$T_{d(off)}$			25		
Turn-Off Fall Time	$t_f$			12		
<b>Source-Drain Diode Characteristics</b>						
Diode Forward Voltage	$V_{SD}$	$I_S = 1\text{A}, V_{GS} = 0\text{V}, T_J = 25^\circ\text{C}$			1.2	V




## P-Electrical characteristics

( $T_A=25^\circ\text{C}$ , unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
<b>Off characteristics</b>						
Drain-source breakdown voltage	$\text{BV}_{(\text{BR})\text{DSS}}$	$V_{GS} = 0\text{V}, I_D = -250\mu\text{A}$	-40			V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS} = -32\text{V}, V_{GS} = 0\text{V}, T_J = 25^\circ\text{C}$			-1	$\mu\text{A}$
Gate-body leakage current	$I_{GSS}$	$V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$			$\pm 100$	$\mu\text{A}$
Gate threshold voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = -250\mu\text{A}$	-1	-1.5	-2.5	V
Drain-source on-resistance	$R_{DS(\text{on})}$	$V_{GS} = -10\text{V}, I_D = -5\text{A}$ $V_{GS} = -4.5\text{V}, I_D = -3\text{A}$		34	43	$\text{m}\Omega$
				45	60	
<b>Switching Characteristics</b>						
Input Capacitance	$C_{iss}$	$V_{DS} = -15\text{V}, V_{GS} = 0\text{V}, f = 1\text{MHz}$		964		pF
Output Capacitance	$C_{oss}$			110		
Reverse Transfer Capacitance	$C_{rss}$			80		
Total Gate Charge	$Q_g$	$V_{DS} = -15\text{V}, V_{GS} = -10\text{V}, I_D = -10\text{A}$		21		nC
Gate-Source Charge	$Q_{gs}$			3.5		
Gate-Drain Charge	$Q_{gd}$			5.2		
<b>Switching Characteristics</b>						
Turn-on Delay Time	$T_{d(on)}$	$V_{DD} = -15\text{V}, V_{GS} = -10\text{V}, R_{GEN} = 3.3\Omega, I_D = -6\text{A}$		5.1		nS
Turn-on Rise Time	$T_r$			15		
Turn-Off Delay Time	$T_{d(off)}$			23		
Turn-Off Fall Time	$t_f$			11		
<b>Source-Drain Diode Characteristics</b>						
Body Diode Voltage	$V_{SD}$	$I_S = -1\text{A}, V_{GS} = 0\text{V}, T_J = 25^\circ\text{C}$			-1.2	V

## N-Channel Typical Characteristics





## P-Channel Typical Characteristics




Figure 1 Output Characteristics




Figure 4 Rdson-Junction Temperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 Rdson-Drain Current







Figure 6 Source-Drain Diode Forward




**Figure 7 Capacitance vs Vds**




**Figure 9 Power Dissipation**



## **Figure 8 Safe Operation Area**




**Figure 10**  $V_{GS(th)}$  vs Junction Temperature



**Figure 11 Normalized Maximum Transient Thermal Impedance**

## PDFNWB5x6-8L-A Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254 REF.		0.010REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	1.470	1.870	0.058	0.074
D2	0.470	0.870	0.019	0.034
E1	3.375	3.575	0.133	0.141
D3	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°