

## Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	$I_D$
40V	6.3mΩ@10V	40A


## Feature

- Low On-Resistance
- Low Input Capacitance

## Application


- Power Management Functions
- DC-DC Converters

## Package




PDFNWB3.3×3.3-8L

## Circuit diagram



## Marking



**40N06** =Device Code  
\* =Month Code

## Absolute maximum ratings

( $T_a=25^\circ\text{C}$  unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	40	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current-Continuous	$I_D$	40	A
Pulsed Drain Current	$I_{DM}$	160	A
Maximum Power Dissipation	$P_D$	41.7	W
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	3	$^\circ\text{C}/\text{W}$
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	$^\circ\text{C}$

## Electrical characteristics

( $T_A=25^\circ\text{C}$ , unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{(\text{BR})\text{DSS}}$	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$	40			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 40\text{V}, V_{GS} = 0\text{V}$			1	$\mu\text{A}$
Gate-Body Leakage Current	$I_{GSS}$	$V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$			$\pm 100$	$\mu\text{A}$
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	1.0	1.5	2.5	V
Drain-Source On-State Resistance <sup>3</sup>	$R_{DS(\text{on})}$	$V_{GS} = 10\text{V}, I_D = 8\text{A}$		6.3	8.5	$\text{m}\Omega$
		$V_{GS} = 4.5\text{V}, I_D = 4\text{A}$		9.5	12	
<b>Dynamic Characteristics</b>						
Input Capacitance	$C_{iss}$	$V_{DS} = 20\text{V}, V_{GS} = 0\text{V}, f = 1\text{MHz}$		1733		$\text{pF}$
Output Capacitance	$C_{oss}$			283		
Reverse Transfer Capacitance	$C_{rss}$			141		
<b>Switching Characteristics</b>						
Turn-On Delay Time	$T_{d(on)}$	$V_{DD} = 20\text{V}, I_D = 2\text{A}, R_L = 1\Omega, V_{GS} = 10\text{V}, R_G = 3\Omega$		3.5		$\text{nS}$
Rise Time	$T_r$			3.7		
Turn-Off Delay Time	$T_{d(off)}$			17.1		
Fall Time	$T_f$			6.4		
Total Gate Charge	$Q_g$	$V_{DS} = 20\text{V}, I_D = 20\text{A}, V_{GS} = 10\text{V}$		8.3		$\text{pF}$
Gate-Source Charge	$Q_{gs}$			2.4		
Gate-Drain Charge	$Q_{gd}$			3.4		
<b>Diode Characteristics</b>						
Diode Forward Voltage	$V_{SD}$	$V_{GS} = 0\text{V}, I_S = 1\text{A}$			1.2	V
Reverse Recovery Time	$t_{rr}$	$T_J = 25^\circ\text{C}, IF = 20\text{A}$ $di/dt = 100\text{A}/\mu\text{s}^{(3)}$		19.8		$\text{nS}$
Reverse Recovery Charge	$Q_{rr}$			8.8		$\text{nC}$
Forward Turn-On Time	$t_{on}$	Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD)				

## Typical Characteristics




Figure 1. Typical Output Characteristic




Figure 2. Typical Transfer Characteristic




Figure 3. Typical On-Resistance vs. Drain Current and Gate Voltage




Figure 4. Typical Transfer Characteristic




Figure 5. Typical On-Resistance vs. Drain Current and Temperature




Figure 6. On-Resistance Variation with Temperature




Figure 7. On-Resistance Variation with Temperature




Figure 8. Gate Threshold Variation vs. Junction Temperature




Figure 9. Diode Forward Voltage vs. Current




Figure 10. Typical Junction Capacitance




Figure 11. Gate Charge




Figure 12. SOA, Safe Operation Area



ZL MOSFET

ZL40N06






Figure 13. Transient Thermal Resistance

## PDFNWB3.3×3.3-8L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.650	0.850	0.026	0.033
A1	0.152 REF.		0.006 REF.	
A2	0~0.05		0~0.002	
D	2.900	3.100	0.114	0.122
D1	2.300	2.600	0.091	0.102
E	2.900	3.100	0.114	0.122
E1	3.150	3.450	0.124	0.136
E2	1.535	1.935	0.060	0.076
b	0.200	0.400	0.008	0.016
e	0.550	0.750	0.022	0.030
L	0.300	0.500	0.012	0.020
L1	0.180	0.480	0.007	0.019
L2	0~0.100		0~0.004	
L3	0~0.100		0~0.004	
H	0.315	0.515	0.012	0.020
$\theta$	9°	13°	9°	13°